# WING

## WAITING AND COMMUNITY CHAIRS

**Specifications**

| | |
|---|---|
| **Structure** | Polypropylene shell in: black, white, tiffany, dove grey colour |
| **Frame** | Four-legged base in polypropylene black, white, tiffany blue, dove grey colour or in wood fibre |
| **Padding** | Flexible polyurethane foam pad 1,5 cm thick, density 40 rc |
| **Castors** | AR8 ø50, polyamide |
| **Swivel base** | 4-spokes pyramidal base in black or white nylon on items 182/183<br>5-star black or white nylon on item 184 |



Via Umbria, 4 - 35043, Monselice (PD) Italy
**arte-d.it**

**In. Fb. Ig.**

**Components and/or modules**

| Image | Dimension | | Code | Description |
|---|---|---|---|---|
| | H | 36 | 180 | Polypropylene shell |
| | L | 57 | | |
| | P | 54 | | |
|  | H | 47 | 181 | Polypropylene 4-legged base |
| | L | 48 | | |
| | P | 46 | | |
| | H | 76 | N182B | Swivel armchair, polypropylene shell, black nylon pyramid base |
| | L | 57 | | |
| | P | 67 | | |
| | H | 76 | N183B | Swivel armchair, polypropylene shell, black nylon pyramid base on castors |
| | L | 57 | | |
| | P | 67 | | |
| | H | 76 | B182B | Swivel armchair, polypropylene shell, 4-spokes white nylon pyramid base |
| | L | 57 | | |
| | P | 67 | | |
| | H | 76 | B183B | Swivel armchair, polypropylene shell, white 4-spokes nylon pyramid base on castors |
| | L | 57 | | |
| | P | 67 | | |
| | H | 75-87 | N184G | Swivel armchair, polypropylene shell, gas pump, black base |
| | L | 57 | | |
| | P | 64 | | |



Via Umbria, 4 - 35043, Monselice (PD) Italy
**arte-d.it**

**In. Fb. Ig.**

| Image | Dimension | | Code | Description |
|---|---|---|---|---|
| | H | 75-87 | B184G | Swivel armchair, polypropylene shell, gas pump, white base |
| | L | 57 | | |
| | P | 64 | | |
|  | | | PS180 | Upholstered seat pad |

**Plastic shell colors**

N BLACK



B WHITE

GT DOVE GREY

TF TIFFANY



Via Umbria, 4 - 35043, Monselice (PD) Italy
**arte-d.it**

**In. Fb. Ig.**

## Coverings

| Cat. | Covering | | Description | Certifications | Folder Colors |
|---|---|---|---|---|---|
| 1 | | **Madrid** *5 colors* | Weight: ± 230 g/sqmComposition: 100% PP polypropylene F.R. Martindale: 80,000 cycles | OEKO-TEX STANDARD 100 Fire proof class 1IM | |
| 1 | | **Cove** *5 colors* | Weight: ± 565 g/sqm Composition: 82% PVC – 7% Cotton – 11% Polyester Martindale: 50,000 cycles | | |
| 2 | | **Angel** *13 colors* | Weight: ± 228 g/sqm Composition: 100% polypropylene F.R. Martindale: 100,000 cycles | Fire proof class 1IM | |
| 2 | | **One** *15 colors* | Weight: ± 350 g/sqm Composition: 100% recycled polyester Martindale: 100,000 cycles | OEKO-TEX STANDARD 100 RECYCLED FROM BOTTLES Fire proof class 1IM | |
| 2 | | **Gazebo** *15 colours* | Weight: ± 640 g/sqm Composition: 87.5% Plasticized Polyvinyl Chloride – 4.4% Cotton- 8.1% Polyester Martindale: 50,000 cycles | Fire proof class 1IM | |
| 2 | | **King-flex** *15 colours* | Weight: ± 300 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles | trevira CS OEKO-TEX STANDARD 100 Ecolabel Fire proof class 1IM | |

## Certifications

ISO 9001 · ISO 14001 · ISO 45001 · FSC · COSMOB · CATAS MEMBER · OMOLOGATO CLASSE 1 IM

Ministerial Homologation Class 1IM on request. Search for FSC® products

https://www.arte-d.it/magic/wing/



Via Umbria, 4 - 35043, Monselice (PD) Italy
**arte-d.it**

**In. Fb. Ig.**

## GENERAL INFORMATION

If the chair is used as a Computer station, the angles between the foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

## GAS PUMP

Instructions for use: The height adjustment of the seat by gas pump is obtained by pulling the lever of the mechanism upwards.
Maintenance instructions: the pump does not require any particular maintenance but it is advisable to avoid direct contact with the sliding parts as they contain lubricant. Warnings: Do not open the gas column by force. Specialized staff only can replace or repair the gas pump.

## PADDED PARTS

Care instructions:
Leatherette: Clean with a damp cloth, mild soap and rinse well with water. It is imperative to avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, light-coloured materials cannot be put in contact with clothes containing unfixed dyes (e.g. jeans and derivatives) in order to avoid stains or streaks that are difficult to remove.
Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would change the fire behaviour of the fabric. Gently dab from the edges to the centre of the stain, do not rub. After stain removal, it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.
Leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth dampened with water and neutral soap by making regular circular movements. Dry gently after treatment. Gently dab from the edges to the centre of the stain, do not rub. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.
Wool: Use the vacuum cleaner regularly with a smooth nozzle, without brushing or scrubbing in any way. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.
Warnings: Some upholstery (leather, imitation leather, weft fabrics) may have a slightly different aesthetic result depending on the batch, the dyeing bath and the product to be made. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change appearance and texture over time, this is to be considered normal.

## UNPADDED PARTS

Care instructions:
Mesh: Use the vacuum cleaner regularly with a smooth spout, without brushing or scrubbing in any way. Any stains can be removed using a cloth dampened with water and neutral soap with regular circular movements. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.
Exposed wood: Clean using a dry cotton cloth to remove any dust residue or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powder cleaners that may damage the paintwork. avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wooden surfaces, being a natural material themselves, may undergo colour alterations with use and over time.
Plastic: Plastic surfaces should generally be cleaned with a damp and soft cloth soaked in water, it is not recommended to use dry cloths that could load with rubbing
electrostatically the plastic surface by attracting dust. For more stubborn stains, neutral liquid soap can be diluted in water in moderation. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as washing powders, abrasive pastes, scouring pads or rough sponges. Avoid dragging objects that can scratch the material on surfaces.

## PAINTED / CHROME-PLATED METAL BASES AND STRUCTURES

Maintenance and cleaning instructions: Both steel or aluminum metal surfaces and painted surfaces should be cleaned with a damp, soft cloth soaked in warm water; For more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois skin. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and scouring pads that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as but not limited to muriatic acid, ammonia, rubbing alcohol, bleach, sulphuric acid, soda, etc.

## CASTORS

Tips: When using the chair on tiled floors, carpets or rugs, we recommend the use of polyamide castors. For stone, wood, laminate floors, we recommend the use of soft desmopan rubber castors. Maintenance and cleaning instructions: It is advisable to clean the castors periodically to avoid the accumulation of dirt that can cause malfunction. Warnings: Do not stress the sliding of the castors on floors with pronounced joints as the difference in height can cause them to break.



Via Umbria, 4 - 35043, Monselice (PD) Italy
**arte-d.it**